



# Test Report Specifications 1150 Fixed Picture Window



**AMAA/WDMA/CSA 101/I.S.2/A440-08, NAFS  
AAMA/WWDA/CSA 101/I.S.2/A440-05  
Report # 69208.03-701-47  
NAMI Certification NI 009342**

## Summary of Results

Title	Specimen 1
Rating	<b>DP F-C60</b> 60 x 72
Design Pressure	± 60.0 psf
Air Infiltration	0.02 cfm/ft <sup>2</sup>
Water Resistance Pressure	12.0 psf
Uniform Structural Pressure	90.0 psf
Forced Entry	Grade 10

**NFRC 102/2010 & 100/200/500  
Report # B5782.10-116-45 / B5783.05-116-46**

Base Unit Validated 47.25" x 59.00"	
Simulated Thermal Transmittance (U-Factor)	0.32

## Specific Thermal Results

*\* Indicates standard options*

Low-E Type W / SuperSpacer	E-Max* (Low-e <sup>2</sup> ) w/ Argon		Advanced E-Max (Low-e <sup>3</sup> ) w/ Argon		Advanced E-Max & I89 (Low-e <sup>3</sup> ) w/ Argon Specifically designed for the Northern Zone	
	No Grids	w/ Grids	No Grids	w/ Grids	No Grids	w/ Grids
<b>U-Factor</b>	<b>0.27</b>	<b>0.29</b>	<b>0.27</b>	<b>0.28</b>	<b>0.23</b>	<b>0.23</b>
<b>SHGC</b>	<b>0.31</b>	<b>0.28</b>	<b>0.23</b>	<b>0.21</b>	<b>0.23</b>	<b>0.21</b>
VT	0.58	0.52	0.54	0.48	0.53	0.47
CR	62	62	62	62	49	49